



CAFITESSE™

NEXT GENERATION COFFEE SYSTEM



INTRODUCING THE NEXT GENERATION IN COFFEE DISPENSERS – HOT AND ICED COFFEE ALL IN ONE

Offer fresh, high-quality hot coffee, or both hot and iced coffee from one easy-to-use dispenser with an appealing new contemporary design.



NG-300 with traditional handles
(also available with buttons instead of handles for increased drink variety)

NG-110 dispenser
(shown with alternate hot/cold graphic, available upon request for either the NG-110 or NG-300)

CAFITESSE NEXT GENERATION SYSTEM BENEFITS:

CONSISTENT QUALITY

The finest coffee beans and our expert brewing process ensure exceptional coffee your customers can count on every day, every time

LESS LABOR

No internal parts to remove or clean and less than 5 minutes per day to maintain; freeing up employees' time to manage other foodservice offerings or to serve customers

ZERO WASTE

Coffee is always fresh—no need to pour out stale coffee and no pilferage

IMPRESSIVE VARIETY

Multiple buttons and optional pre-selection choices for hot/cold temperature, cup size, and coffee strength enable a wide variety of beverage options

RELIABLE EQUIPMENT

Our state-of-the-art equipment averages only one service call per year, ensuring maximum uptime

DEDICATED SUPPORT

Nationwide service network is available 24/7/365 to keep your coffee business running smoothly



NG-110 Ideal for 35+ cups/day*

Serves a single blend of coffee, plus hot water. Ratios can be adjusted to deliver a regular or bold/high-caffeine coffee from same machine. Dispenser can be configured to dispense hot coffee only or a combination of both hot and iced coffee.

FLOW RATE & HOURLY CAPACITY* (12 oz cup with 10 oz fill)	DISPENSER WEIGHT EMPTY TANK / FILLED TANK DIMENSIONS	ELECTRICAL & WATER SUPPLY
<p>Hot Coffee Flow Rate: 145 oz/minute Iced Coffee Flow Rate: 91 oz/minute</p> <p>Hot Coffee Hourly Capacity – 180°F Water Inlet: 865 cups/hour</p> <p>Hot Coffee Hourly Capacity – 55°F Water Inlet: @ 120v-15a = 66 cups/hour @ 208v-20a = 139 cups/hour @ 208v-30a = 205 cups/hour @ 208v-50a = 328 cups/hour</p>	<p>68.3 lbs / 92.6 lbs</p> <p>H 31" (35" with airpot kit)</p> <p>W 10.2"</p> <p>D 20.5"</p> <p>Maximum cup height: 8.3"</p> <p>Maximum cup height with airpot kit 13.0"</p>	<p>110v: 15 amp circuit 208-240v: 20 amp circuit (4-wire outlet) 208-240v: 30 amp circuit (4-wire outlet) 208-240v: 50 amp circuit w/ optional high current kit (4-wire outlet)</p> <p>3/8" water line 20-90 psi</p> <p>NSF UL</p>



NG-300 Ideal for 60+ cups/day*

Serves up to two different blends of coffee, plus hot water. Dispenser can be configured to dispense hot coffee only or a combination of both hot and iced coffee. Available with traditional handles or multiple beverage push-buttons.

FLOW RATE & HOURLY CAPACITY* (12 oz cup with 10 oz fill)	DISPENSER WEIGHT EMPTY TANK / FILLED TANK DIMENSIONS	ELECTRICAL & WATER SUPPLY
<p>Hot Coffee Flow Rate: 145 oz/minute Iced Coffee Flow Rate: 91 oz/minute</p> <p>Hot Coffee Hourly Capacity – 180°F Water Inlet: 865 cups/hour</p> <p>Hot Coffee Hourly Capacity – 55°F Water Inlet: @ 120v-15a = 66 cups/hour @ 208v-20a = 139 cups/hour @ 208v-30a = 205 cups/hour @ 208v-50a = 328 cups/hour</p>	<p>80.5 lbs / 105.2 lbs</p> <p>H 31" (35" w/airpot kit)</p> <p>W 13.8"</p> <p>D 20.6"</p> <p>Maximum cup height: 8.3"</p> <p>Maximum cup height w/airpot kit 13.0"</p>	<p>110v: 15 amp circuit 208-240v: 20 amp circuit (4-wire outlet) 208-240v: 30 amp circuit (4-wire outlet) 208-240v: 50 amp circuit w/ optional high current kit (4-wire outlet)</p> <p>3/8" water line 20-85 psi</p> <p>NSF UL</p>



OPTIONAL HOT/COLD GRAPHICS & BUTTONS FOR NG-110 AND NG-300

Hot/cold dispenser graphic/button kits available upon request or upon order from Sara Lee Foodservice POS Fulfillment site

PLEASE CONTACT YOUR SARA LEE SALES REPRESENTATIVE FOR MORE INFORMATION OR CALL 1-800-373-6705.

*12 oz. cup with 10 oz. fill at 28:1 water-to-coffee ratio setting (2.75 oz. throw weight)