



The New Dimension of Pure

DESIGNED TO BE THE TOP ENVIRONMENTALLY-FRIENDLY DRINKING WATER SYSTEM FOR YOUR WORKPLACE

The EcoStream™ proprietary system dispenses pure, clean drinking water while reducing the environmental impact of bottled water systems. The sleek outer design houses a microprocessor controlled system that delivers a continuous supply of hot and cold drinking water — perfect for any workplace.

FEATURING



Multi-Stage Process

- Stage 1: Sediment Removal
- Stage 2: Taste & Odor Removal
- Stage 3: Ultraviolet Disinfection

- ◆ Filter & UV Monitor
- ◆ Touch Tone Dispensing
- ◆ In Tank UV Sanitation
- ◆ Leak Lock™ Detector
- ◆ 11 ½ “ Cup Clearance
- ◆ Tri Temperature
- ◆ Bio Guard™ Protection
- ◆ Digital Program
- ◆ Energy Star
- ◆ Convenient filter change
- ◆ Easy maintenance access
- ◆ Energy Star certified



Aurora POU Water Cooler	Classic Floor #3002	Classic Table Top #3003	Tri Temp Floor #3000	Tri Temp Table Top #3001
Power Consumption	90W/450W	90W/450W	90W/450W	90W/450W
Temperature Cold Tank	37-50°F	37-50°F	37-50°F	37-50°F
Temperature Hot Tank	167-189°F	167-189°F	167-189°F	167-189°F
Temperature Ambient	N/A	N/A	68-74°F	68-74°F
Storage Capacity Cold Tank	1 Gallon	1 Gallon	1 Gallon	1 Gallon
Storage Hot Tank	1/2 Gallon	1/2 Gallon	3/4 Gallon	1/2 Gallon
Dispensing	Dual Separate Levers	Dual Separate Levers	Electronic Touch	Electronic Touch
In Tank Sanitization	Ultra Violet	Ultra Violet	Ultra Violet	Ultra Violet
Sanitization Parts	UV Bulb/ 1 Year Life	UV Bulb/ 1 Year Life	UV Bulb/ 1 Year Life	UV Bulb/ 1 Year Life
Leak shut off	Leak Lock	Leak Lock	Internal	Internal
Filter Monitor	LED and LCD Actual	LED & LCD Actual	LED Actual	LED Actual
Cup Clearance	8 inches	8 inches	11 1/2 inches	11 1/2 inches
Electrical Certification	UL under TUV	UL under TUV	UL under TUV	UL under TUV
Contaminant Certifications	ANSI/NSF 51 under WQA	ANSI/NSF 51 under WQA	ANSI/NSF 51 under WQA	ANSI/NSF 51 under WQA
Energy Star Listed	Yes	Yes	Yes	Yes
Antibiotic Coating	Yes	Yes	Yes	Yes
Control Type	Mechanical	Mechanical	Digital	Digital
Temperature Control	Thermostat	Thermostat	Thermostat	Thermostat
Heater	Bi Metal External	Bi Metal External	Seath Internal	Seath Internal
Weight	45 Pounds	40 Pounds	60 Pounds	55 Pounds
Dimensions (WxDXH)inches	15.35"(W)X13"(D)17.70"(H)	15.35"(W)X13"(D)17.70"(H)	15.35"(W)X13"(D)43.30"(H)	15.35"(W)X13"(D)17.70"(H)



ISO 9001:2000 (E)



www.cdcoffee.com